

PRODUCT CATALOG

Unleash the power of our cutting-edge technology, which not only offers superior grass cutting capabilities but also allows you to effortlessly switch between multiple attachments for tasks like loading, snow pushing, and orchard spraying. With our all-in-one solution, your equipment costs and maintenance expenses will significantly decrease, while your overall productivity and economic benefits soar.

Tiller Machine



+86 13255503588
tony@grmaterial.com
www.zhier-tech.com



Product Feature

1. Front Rotating Tilling and Rear-Drive: Power and Precision Combined

Experience the perfect balance of power and precision with our micro tiller's front rotating tilling and rear-drive system. This ingenious design ensures optimal soil cultivation, providing unmatched efficiency in your farming endeavors.

2. Differential Steering and Four-Wheel Drive: Conquering All Terrain

Embrace the versatility of our micro tiller with differential steering and four-wheel drive capabilities. Effortlessly navigate through any terrain with ease, allowing you to conquer various landscapes and agricultural tasks with confidence.

3. Low-Profile Design: A Universal Fit for All Users

With a low-profile body, our micro tiller accommodates a wide range of users. From seasoned farmers to beginners, everyone can effortlessly operate our machine, making it an ideal choice for farmers of all experience levels.

4. Adjustable Working Width: Precision at Your Fingertips

Our micro tiller grants you full control with adjustable working widths. Customize the tiller's width to suit your specific needs and crop requirements, ensuring precise cultivation and maximizing productivity.

Discover the epitome of efficiency and versatility with our micro tiller. Embrace power, precision, and user-friendliness like never before. Unleash the potential of your farming efforts with us today!





Product Specification

Model: 3TG-4Q-F	
Structure	Front -mounted Engine
Engine model	170/177 Gasoline/173/178 Diesel
Rated power	4/4.5KW and 4.05/4KW
Dimension (L*W*H)	157 * 35 * 58 cm
Weight	80-120kg
Transmission mode	Four-wheel drive self-propelled
Type Connection mode	Direct connection knife roll
Rotate speed	450r/min
Knife roll Max.turning radius	400mm
Knife roll number of blades	24pcs
Model of rotary blade	175mm
Main clutch type	Tensioner
Rotary tilling width	150-200mm
Rotary tilling depth	400-800mm
Ditching width	200-400mm (Adjustable)
Ditching depth	300mm
Operating speed	≧ 0.5km/h
Productivity	1-1.5acres/h
Fuel consumption	0.7-1.2L/h
Wheel size	330mm